



Samsung Galaxy J5 2017 Display Replacement

Follow this guide to replace the display in a Samsung Galaxy J5 2017.

Written By: Smilzo



INTRODUCTION

Use this guide to replace a cracked or dead screen in your Samsung Galaxy J5.

If the frame is warped, it is important to replace it to make sure the new screen fits properly and does not suffer damage from uneven pressure.

Before disassembling your mobile, discharge the battery below 25%. The battery could catch fire and / or explode if accidentally punctured, but the chances are much lower if it is discharged.

Note: This guide tells you how to replace the screen only, leaving the original chassis and motherboard in place. However, some replacement screens come pre-installed in a new chassis, which requires a very different procedure. Make sure you have the correct part before you start following this guide.

You will need replacement adhesive to re-glue the components when reassembling the device.



TOOLS:

- [iOpener](#) (1)
 - [Suction Handle](#) (1)
 - [SIM Card Eject Tool](#) (1)
 - [iFixit Opening Picks \(Set of 6\)](#) (1)
 - [Tweezers](#) (1)
-

Step 1 — Display



- With a hair dryer, heat the glass well so that the adhesive glue can detach easily.
- ⓘ Use thin tools all over the profile and insert them between the plastic frame and the glass.
- ⚠ Do not insert the opening tools you are using between the aluminum and the plastic frame.

Step 2



- Lift the display from bottom to top where the flat and connector is connected.
- Remove the black snap-on lid.
- Unclip the connector.
- Thoroughly clean the surfaces of glue residues and install the replacement display.

To reassemble the device, follow these instructions in reverse order.