



Fender Champion 600 Teardown

Written By: in_sympathy





TOOLS:

Pro Tech Toolkit (1)

Step 1 — Fender Champion 600 Teardown



 **WARNING:** First of all disconnect an amp from the power outlet!

 Please be careful - Tube amps can hold a serious amount of electrical charge that can cause injuries or even death. Avoid touching any wires or contacts with your bare hands or instruments that have no reliable insulation.

Step 2



- Let's start by removing the rear chassis screws. All of the screws we are going to deal with work nicely with a PH2 bit.
- Then remove two side screws that also hold the amp chassis in place. Those are 4 x 30 mm btw.

Step 3



- Below the chassis you'll find 4 more phillips screws holding a rear cover in place - remove them as well.

Step 4



- Now it's time to remove the nuts on the input jacks and our broken volume pot - I used pliers to do that, but it is advisable to use a small adjustable wrench, combination wrench, or socket in order to avoid any unwanted scratches or damage.

Step 5



- Next let's remove the volume knob - you'll need a flat 2.5 bit for that. Carefully insert the bit into the hole on the rear side of the knob to undo a tiny screw inside of it.
- That's it - chassis is free .
- Hint: use a plastic tray or a [magnetic mat](#) to safely store all of those screws and nuts. You can even write where all those parts come from.

Step 6



- Slightly lift it up and pull towards you with just a hand to access the internals.
 - That's it - the amp's chassis is right in front of you.
 - Well done
-