



Hemming Pants

Use this guide to hem your pants, adjusting them to the desired length.

Written By: Brittany McCrigler



INTRODUCTION

Overly long pants will bunch up at the ankles, and may even drag along the ground or get caught under your shoes. (If you thought last season's styles were embarrassing, try tripping over your own pants.) Use this guide to avoid fashion faux pas by hemming your pants to suit.

For replacement parts or further assistance, contact [Patagonia Customer Service](#).

TOOLS:

- [Sewing Pins](#) (1)
 - [iFixit 6 Inch Metal Ruler](#) (1)
 - [Sewing Machine](#) (1)
 - [Utility Scissors](#) (1)
 - [Fabric Scissors](#) (1)
-

Step 1 — Hemming Pants



- Begin by assessing the pants' current length. This is best done by wearing the pants along with an appropriate pair of shoes.
- ⓘ Wearing pants barefoot or with high heels will affect their length relative to the floor.
- ⓘ It's helpful to have a second person assist with this step and the two that follow.

Step 2



- Fold the cuff of one pant leg inward, and adjust it to the desired length.
- Insert two or three pins to hold the cuff in position.
 - The pins should be placed parallel to the new fold.
- With the pins in place, verify that the length is correct.
- Make any final adjustments to the length as needed.

Step 3



- On a flat, clean surface, lay the pants down on their side with the newly shortened pant leg on top.
- Using a ruler, note the distance from the edge of the old cuff to the edge of the new cuff.
- Repeat the measurement several times along the width of the cuff, making sure the new hemline is perfectly even.

Step 4



- Thread the sewing machine, using a thread color that matches your garment's fabric as closely as possible.
- ⓘ Sewing machine setup varies from one model to another. Consult your sewing machine manual for precise instructions.
- Place the first cuff on the sewing machine, and position the sewing needle between one of your pins and the edge of the cuff.

Step 5



- Gently depress the foot pedal and begin sewing.
- ⚠ Be sure the needle penetrates the pant leg on only one side. It may be easier to position the pant leg around the arm of the sewing machine with the table removed. If you sew through both layers, you will sew the pant leg shut!
- Pause when you reach a pin, and remove it before continuing.
- ⚠ Do not attempt to sew over any pins. Hitting a pin can bend or break the sewing machine needle.

Step 6



- Continue sewing all the way around the cuff, until you reach the first few stitches.
- Sew over the first few stitches to prevent the stitches from unraveling.

Step 7



- Raise the presser foot, and remove the pants from the sewing machine.
- Clip any threads.

Step 8



- Turn the cuff over so that the extra length of the hem folds out.
 - Clip the extra length, leaving about a half inch of fabric beyond the seam.
- ⚠** Be sure to only cut through one layer of the fabric—the excess fabric. Do not cut through the pants.
- i** This step is optional. If you are hemming pants for a growing kiddo, leaving the excess length allows you to rip the seam and magically lengthen the pants later on.

Step 9



- Set your sewing machine to a zigzag stitch.
 - Insert the freshly cut edge of the hem into the sewing machine.
- ⚠** Be sure to only insert one layer of fabric—the hem—or you will sew through the outer, visible layers of the pants.

Step 10



- Sew around the hem, as close to the edge as possible.
- ⓘ Zigzagging the edge prevents the edge from unraveling.

Step 11



- Lift the presser foot and remove the pants from the sewing machine.
- Clip any excess threads.

Repeat steps 5-19 for the second pant leg.