



iPad 2 Touch Screen Replacement Video tutorial

Written By: ZFix



INTRODUCTION

Don't try this if you haven't experience !!!

How to replace / change broken glass / touch screen - Apple iPad2.

See also [iPad 2 Wi-Fi EMC 2415 Front Panel Replacement](#)

[Please SUBSCRIBE to my channel ツ](#)

[video: <https://www.youtube.com/watch?v=Z6uGw5Abla8>]

TOOLS:

- [iFixit Opening Picks set of 6](#) (1)
 - [iOpener](#) (1)
 - [Phillips #00 Screwdriver](#) (1)
 - [iFixit Opening Tools](#) (1)
-

Step 1 — Front Panel Assembly



- Use the edge of a plastic opening tool to carefully flip up the retaining flaps on the two digitizer ribbon cable ZIF sockets.

⚠ Be sure you are prying up on the hinged retaining flaps, **not** the sockets themselves.

ⓘ The retaining flaps are highlighted in red in the second picture.

Step 2



- Use the edge of a plastic opening tool to peel the digitizer cable off the shields on the logic board.
- Carefully pull the digitizer cable off the adhesive securing it to the side of the rear case.

Step 3



- Pull the digitizer ribbon cable straight out of its two sockets on the logic board.

Step 4



i In order to remove the front panel assembly, the ribbon cable needs to slide out between the case and the LCD. You'll need to move the LCD to make some room.

⚠ Be very careful when moving the LCD, and do not attempt to remove it from the iPad—its cable will remain connected while it is rotated over.

- Lift the LCD from its long edge farthest from the digitizer cable and gently flip it toward the rear case—like closing a book.
- While holding the LCD up, gently slide the front panel away from the iPad. Be careful not to snag the digitizer cable on the rear case or LCD.
- Set the LCD back into the body for safekeeping.

To reassemble your device, follow these instructions in reverse order.