



# MAGNAVOX MDV2300 Power Cord Replacement

How to change the MAGNAVOX MDV2300 power cord.

Written By: Justin



---

## INTRODUCTION

We will be showing you step by step how to access the power cord and replace it by soldering a new one in.



### TOOLS:

- [Phillips #0 Screwdriver](#) (1)
  - [Soldering Iron](#) (1)
  - [Solder](#) (1)
-

## Step 1 — Power Cord



- Make sure the device is unplugged from the wall.

## Step 2



- Unscrew the two screws that hold together the top panel.

### Step 3



- Remove the top panel.


### Step 4



- Remove the motherboard to access the interior of the device.
- ⓘ See "removing the motherboard guide" for details on how to complete this step. [MAGNAVOX MDV2300 Motherboard Replacement](#)



## Step 5




- Remove disc drive by unscrewing the 2 screws that hold the drive in place.

## Step 6



- Identify the power cord.
- ⓘ The cord must either be too short or torn to warrant replacement.

## Step 7



- Cut the old wire out from the chip.
  - Attach the new wire into the housing.
  - Line up new wire with the appropriate holes and solder to board.
- ⓘ The white wire will be your neutral and the black wire will be your negative. View link of how to solder in order to replace the power cord.  
<http://www.instructables.com/id/How-to-s...>

After soldering, let cool and then reassemble your device, follow these instructions in reverse order.