




# Samsung Gravity TXT Keyboard Replacement

This Guide is for replacing the keyboard.

Written By: Hussain






## TOOLS:

- [iFixit Opening Tools](#) (1)
  - [Phillips #00 Screwdriver](#) (1)
  - [Jimmy](#) (1)
  - [iFixit Opening Picks set of 6](#) (1)
-

## Step 1 — Battery



- Pry the back cover off with a plastic opening tool, or your fingernail, in the indentation on the bottom of the device.


## Step 2



- Lift the back cover away from the main body of the phone.





### Step 3



- Insert your finger in the groove below the battery.
  - Press the battery toward the audio jack while lifting upward and away from the phone.
- ★ Remember to place the battery back with the copper contacts on the battery lined up with those on the phone.

### Step 4 — SIM Card




- Using your finger, push the SIM Card down and slide out of the slot.
    - ❗ Slide the SIM card out enough to grab it firmly.
  - Remove the SIM card away from the phone.
- ★ Follow the visual on the bottom of the SIM card slot to put the SIM card back in the correct orientation.
- ❗ When sliding the SIM Card back in the slot, make sure the card goes all the way in the slot until it hits the stopper.

## Step 5 — microSD Card



- Using your fingernail, push the microSD card slightly deeper into the slot, until you hear a click.
- ⓘ The removal of the battery is not required for this operation; therefore, step 3 can be skipped if just replacing the microSD card.
- After the click, release the microSD card to allow it to pop out.
- Remove the microSD card from its slot
- ☑ When placing the microSD card back in the phone, make sure the card clicks in place.

## Step 6 — Plastic Back Frame



- Remove the six 3 mm #00 Phillips screws in the plastic back frame.




## Step 7




- Slide the keyboard out.
- Use a Jimmy to separate a small segment of the plastic back frame from rest of the phone.
  - ⓘ Starting at the bottom of the keyboard is recommended.
- Slide an opening pick around the rest of the seam, starting at the gap just created with the Jimmy.
  - ⓘ You will have to slide the keyboard back in to separate the back frame from the top half of the keyboard slider.
- Lift the plastic back frame away.

## Step 8 — Motherboard




- Remove the two 3 mm Phillips #00 screws securing the motherboard to the front panel.
- ⚠ Do not try to pull the motherboard out just yet. The display data cable needs to be disconnected from the motherboard first.

## Step 9



- Use your finger nail to disconnect the display data cable from the motherboard.


## Step 10



- Carefully lift the main motherboard assembly away from the front panel.



## Step 11 — Keyboard



- Take the keyboard off of the phone.

To reassemble your device, follow these instructions in reverse order.