



HTC One X Plus Antenna Replacement

If rebooting your device or updating the...

Written By: Jason Melo



INTRODUCTION

If rebooting your device or updating the software to the latest version doesn't solve your Wi-Fi or Bluetooth connectivity, then replace your HTC One X+ antenna.

TOOLS:

- [Tweezers](#) (1)
 - [Suction Handle](#) (1)
 - [Phillips #000 Screwdriver](#) (1)
 - [Spudger](#) (1)
 - [iFixit Opening Tool](#) (1)
-

Step 1 — Antenna



- Power off your device.
 - Insert a pin, paper clip, or very small piece of metal into the hole next to the micro-SIM card holder to remove it.
- i** The SIM card slot is located on the top edge of the device.

Step 2



- Using the plastic opening tools, pry open the bottom of the device first.
- You will hear clicking sounds as the sides of the device detach from the screen.
- Once both sides are detached, use the suction cup tool to remove the screen completely from the black encasing.

Step 3



- Now that the rear panel has been removed, use the metal tweezers to carefully remove the antenna.
 - The antenna is the loose black wire located to the right of the battery.
- Using the metal tweezers, connect and install your new antenna, securing the antenna beneath the metal supports.

To reassemble your device, follow these instructions in reverse order.