



ASUS D550MA-DS01 Screen Replacement

This guide will show you how to replace your laptop screen.

Written By: Calvin Wieczorek



INTRODUCTION

Many people will dump a laptop if the screen is broken, but this laptop's screen is replaceable! This guide will walk you through how to remove your screen module so that it may be replaced.

TOOLS:

- [Phillips #1 Screwdriver](#) (1)
 - [Spudger](#) (1)
 - [Tweezers](#) (1)
-

Step 1 — Keyboard Module



i Before you begin, be sure to turn off your laptop and unplug it from the outlet.

- Use a Philips #1 screwdriver to remove the nine screws from the back cover.



Step 2



- Turn the laptop over and open the display.
- Insert the flat edge of the spudger into the crease of the keyboard cover.
- While the spudger is in the crease, carefully pry open the casing by sliding the spudger along the edge.


! Do not use excessive force to pry open the lid. You should hear each plastic clip snap open as you run the spudger along the edge.

Step 3



- ① Make sure that the entire cover has been released from the plastic clips.
- Slowly lift the cover open from the front of the laptop, but do not completely remove it.
- Note the locations of the three white and blue data cables connecting to the keyboard to the computer's main board.

Step 4





- i If you are only replacing the battery, you can skip this step and the next. Shift the keyboard module away from the display and set it such that the fragile flex cables are not strained.
- Disconnect the three data cables from the motherboard.
- i To unlock a [ZIF connector](#), use the tip of a spudger or your fingernail to flip up the small, hinged locking flap. Carefully slide the unlocked cable out of the socket.


Step 5



- Remove the fully disconnected keyboard module from the laptop.



Step 6 — Battery



 Do not use any metal tool to pry any type of battery. Doing so can puncture or short the battery, resulting in damage or injury.


- Remove the two screws securing the battery to the laptop case with a Phillips #1 screwdriver.

Step 7




- Lift the battery out and remove it:
 - ❗ The battery is connected to the motherboard on the left side.
 - Use your fingertips to evenly grip the battery on the left and right sides of the battery.
 - Pull straight up to lift the battery out of its place.
 - ❗ Do not use excessive force or attempt to pry the battery with any tools. Doing so will result in damage to the laptop.

Step 8 — Hard Drive




- Remove the four screws that hold the hard drive in place with the Philips #1 screwdriver.
- ⓘ There are two screws connected to the motherboard and two screws connected directly to the case.

Step 9




- Remove the hard drive by sliding it to the right to disconnect it from the motherboard and lifting out.
- ⚠ Be sure to fully disconnect the hard drive from the motherboard to ensure that you do not damage the connectors.
- ⓘ If necessary, unscrew the old hard drive from the holster and screw the new one into the holster.

Step 10 — DVD Drive



- Remove the single screw that is holding the drive in place using the Phillips #1 Screwdriver.

Step 11




- Slide the drive out to the right of the laptop to disconnect from the motherboard.
- ⚠ Lifting the drive straight out without sliding to the right will damage the motherboard.

Step 12 — Motherboard




- Remove the 9 screws from the motherboard using the Philips #1 screwdriver.
- ⓘ While unscrewing the screws, it may be helpful to use the tweezers to keep control of the screws.

Step 13



- Disconnect the three cables attached to the motherboard.
- ⚠ Do not pull the cables by their wires. This can lead to damage to the cables.
- The large, black cable is connected to the screen. Carefully wiggle the cable out by gripping the black tape with your fingers.
- ⓘ There may be clear tape holding the screen connector in place.
- The cable for the fan and speaker use similar connectors. Use the black spudger or carefully grip the sides of each connector with your fingers to slowly pull them out.

Step 14




- Pull the motherboard to the right to clear the peripheral connections of the laptop casing.
- Lift the motherboard out of the laptop.


Step 15 — Screen




- Carefully free up the black and white RF cables that are running along the laptop casing and speaker housing.

Step 16




 Following these next steps will remove the Screen Module Anchors. Hold the screen in place as you follow these steps to prevent the screen from dropping.

- Unscrew the 4 screws for the Screen Module Anchors using the Philips #1 screwdriver.

 One screw is on the left anchor while three are on the right anchor.

Step 17



- Carefully lift the screen straight up and away from the laptop base.
-  The white and black RF cables will remain attached to the screen module.

To reassemble your device, follow these instructions in reverse order.