



Motorola V400 Camera Replacement

To complete this guide you will need a pair of...

Written By: Brian Avsec



INTRODUCTION

To complete this guide you will need a pair of tweezers, a Torx T-6 screw driver, and a wedge to pry with. Before you start be sure to turn off the phone, remove the battery, and find a clean, water free work space.

TOOLS:

[T6 Torx Screwdriver](#) (1)

[Tweezers](#) (1)

[iFixit Opening Tool](#) (1)

Step 1 — Camera



 Take out the battery first!!!

- Remove the four rubber stoppers around the main screen with [tweezers](#).

Step 2



- Use a Torx T6 screwdriver to remove the 4 screws around the screen.

ⓘ Note that the top screws are black the the bottom screws are silver and that they are different lengths.

Step 3



- Use a plastic opening tool to separate outer shell from metal interior cover by sliding it along the crease in the case.


⚠ To easily take off the case close the phone before trying to remove it.

Step 4



- Use a plastic opening tool to separate the inner metal cover from the circuit board. Apply pressure to remove the piece.

Step 5



- Remove rubber covering over the camera.
- Carefully remove camera and the attached orange ribbon by gently pulling on it. Pull out in the direction of the blue arrow. You can use your fingers or tweezers.

To reassemble your device, follow these instructions in reverse order.