

# **Gateway Lt4004u Keyboard Replacement**

This is a moderately difficult process. There...

Written By: Carlisle Hiott



#### **INTRODUCTION**

This is a moderately difficult process. There aren't many steps, but make sure you follow the first steps closely to insert the card correctly.

#### TOOLS:

Jimmy (1)
iFixit Opening Picks (Set of 6) (1)

### Step 1 — Battery







- Place the laptop face down in front of you.
- Locate the battery lock switches on the left and right top corners of the bottom of the device indicated by the red circles.
- Pinch the switches and slide toward the edges of the computer to unlock.

# Step 2






- Once the switches have both been unlocked, push the battery upwards away from the rest of the laptop.
- Remove the battery from the laptop.

## Step 3 — Keyboard







- Open the laptop so that the screen and keyboard are facing you.
- Identify the 5 tabs above the function keys in the crevice that attaches the keyboard to the main frame.

### Step 4







- Use an opening pick to push each tab away from you.
- Use an opening tool to push the middle tab until you hear a click. Begin to push the tool downward into the computer and slide the card along the length of the keyboard, as you overcome the five tabs.

🛆 A clicking sound is normal and no cause for alarm.

### Step 5







- Begin to slide the <u>plastic card</u> under the top edge of the keyboard. You will hear popping sounds and the keyboard will eventually be released.
- Carefully pry the keyboard from the main frame, starting at the top section.
- ② Look at the intel sticker in this step and the next to orient your computer with the pictures.

# Step 6





- (i) Look at the intel sticker in this step and the previous step to orient your computer with the pictures.
- Unplug the thin blue connection piece beneath the keyboard. It may pop off on its own while you are prying off the keyboard.
  - ⚠ The popping noise will not hurt the computer.
- Once the thin blue plastic has been detached, remove the keyboard from the rest of the laptop.

To reassemble your device, follow these instructions in reverse order.