



# HP Pavilion 17-f004dx Keyboard Replacement

This guide will show you how to replace your device's keyboard.

Written By: Chi Huynh



## INTRODUCTION


Please note that laptop keyboard removal is not an easy process and will take time and patience, particularly when reinstalling your new keyboard.

---

### TOOLS:


- [Metal Spudger](#) (1)
  - [Phillips #0 Screwdriver](#) (1)
  - [Phillips #1 Screwdriver](#) (1)
  - [iFixit Opening Tools](#) (1)
-

## Step 1 — Battery



- ⚠ Before you remove the battery, make sure the laptop is powered off.
- Slide the black battery latches inward to remove the battery.

## Step 2




- Pull the battery out towards you while your fingers are still holding the latches in place.

### Step 3 — CD Drive




- Remove one 7 mm screw with a Phillips #1 screwdriver.

### Step 4





- Use a metal spudger to push the CD drive out of its slot for removal.

## Step 5 — Front Panel



- Remove fifteen 7 mm screws with a Phillips #1 screwdriver.

## Step 6




- Remove the thin plastic cover using the flat metal spudger to expose another screw.
- Remove one 7 mm screw with a Phillips #0 screwdriver.

## Step 7



- Use a metal spudger to remove the rubber "feet" to expose two screws.

## Step 8



- Underneath each rubber foot, there is a screw.
- Use the Phillips #1 screwdriver to remove a 4.8 mm screw on each side.

## Step 9



- Remove the two black end caps to expose more screws.
- ⓘ The end caps will require some force to remove.

## Step 10



- Remove the following six screws with a Phillips #1 screwdriver:
  - Two 7 mm screws.
  - Two 7 mm screws.
  - Two 4.8 mm screws.

## Step 11



- Remove two 2.4 mm broadhead screws from the CD Drive bay with a Phillips #0 screwdriver.

## Step 12




- Flip the laptop back over. Then, with the laptop open, move the plastic prying tool around the top cover to pry it from the enclosure.

## Step 13




- Partially lift the top cover from the enclosure.

## Step 14




- Remove the ribbon connecting the power button to the motherboard.

## Step 15




- Remove the ribbon connecting the mousepad to the motherboard.

## Step 16





- Remove the ribbon connecting the keyboard to the motherboard.
- You may now fully lift the front panel from the rest of the laptop.

## Step 17 — Keyboard



- Turn the front panel over and partially remove the clear plastic covering the keyboard casing.


## Step 18



 Plastic debris may scatter while lifting the metal housing. These pieces are indicated in red.

- Use a metal spudger to remove the metal housing from the front panel.

## Step 19



- Lift the metal housing from the front panel to separate the keyboard from the top panel.

To reassemble your device, follow these instructions in reverse order.