



# Astro Pyle PTBL7C Battery Replacement

Here are some instructions on how to change the...

Written By: Abdulelah



# INTRODUCTION

Here are some instructions on how to change the old Battery of Astro Pyle PTBL7C and install a new one.

---

## TOOLS:

Spudger (1)

Soldering Iron (1)

---

## Step 1 — Battery



- Use the spudger to open the device from the front edge of the screen. Gently slide it in and push it up to open.
- ⓘ It may emit a cracking sound at it opens; this is only the locks coming apart.

## Step 2




- The battery will appear as pictured. Separate the back case from the device. Avoid damaging the wire that connects the speakers between the two halves of the case.

## Step 3




- The battery is attached in two different ways; one wire is attached to the screen to support the screen's background led lights. Carefully desolder the wire without damaging the part connecting the battery to the screen.

## Step 4




- Desolder the wires pictured. These feed energy from the battery into the motherboard.  
⚠ Use caution to avoid damaging the motherboard or other critical pieces.

## Step 5



- Use a [plastic card](#) to gently break the adhesive holding the battery to the metal screen plate. Remove the battery.  
⚠ Though non-functional, the battery still contains dangerous chemicals. Handle it directly as little as possible.

## Step 6



- Install the new battery and solder all the connections back in place.
    - ① Visit this guide for more information on soldering and desoldering: [iFixit Soldering Guide](#)
- 

To reassemble your device, follow these instructions in reverse order.