



Toshiba Satellite C855D-S5303 Fan Replacement

This guide will show you how to replace your...

Written By: Courtney Burns



INTRODUCTION

This guide will show you how to replace your laptops fan. This process requires only a small Phillips head screwdriver and your hands.

TOOLS:

[Small Phillips Head Screwdriver](#) (1)

Step 1 — Battery



- Lay your laptop upside down on a flat surface.
- Power off your laptop and unplug the charger.

 **Make sure you allow the laptop time to cool so that you aren't removing a hot battery.**

Step 2



- Locate the right eject switch, labeled "1".
- Slide the switch all the way to the right and it should stay in place.

Step 3



- The second eject switch is on the left and it is numbered "2".
- Slide the switch to the left and remain pushing on it, because unlike switch "1" it will not stay in place on it's own.

Step 4



- With hand still pushing the left switch, grab onto notch at the center of the two switches.
- Pull up and towards you. The battery will begin to lift out of the device.

Step 5




- The battery can now be pulled out entirely. You are ready to replace it.

Step 6 — Hard Drive



- Using a small Phillip's head screwdriver, unscrew the single 7 mm screw (5 mm head) on the L-shaped panel on the backside of the laptop.

Step 7



- Once the screw is removed, pry the panel upwards by gripping the groove pictured.

⚠ Be careful while removing the panel. Don't apply too much force when lifting as you may crack the plastic.

Step 8



- Locate the hard drive. It is in a metal casing as pictured.
- To remove, grab the right side of the piece and slide leftwards.
- Lift up and out.

Step 9 — Fan



- Now that you have your battery and hard drive removed, it's time to begin unscrewing the back panel.
- Taking a Phillip's head screwdriver, remove the two 7 mm (5 mm head) screws located around the spot where the hard drive once was.


Step 10



- There are nine 7 mm (5 mm head) screws located around the perimeter of the laptops back panel. Unscrew them all.

⚠ Be sure you put all the screws in a safe spot so you do not lose them.


Step 11



- Get a grip on one edge of the back panel that is now unscrewed and lift its entirety up and away from the device.


⚠ Be gentle when lifting the panel. Do not forcefully pull it off.

Step 12



- ⓘ Upon locating your device's fan, look to see if it is dirty or clogged with dust before continuing with the removal process. That may be your only issue.
- To remove the fan, unscrew the two 4 mm (3 mm head) screws that are around the fan.

Step 13



- Unplug the wire located to the left of the fan by pulling gently upwards.
- ⚠ Remember which way you pulled it out. You will want to replace the fan with the colors on the wire in the same orientation.
- Now that the fan is unplugged, you can lift it up and out of the device.

To reassemble your device, follow these instructions in reverse order.

