



# LG Volt LS740 Charging Port Replacement

Guide to replace LG Volt LS740 Charging Port

Written By: SMcC21985



## INTRODUCTION

Found this in the bottom of a closet and through some troubleshooting decided the charging port was broken.

Couldn't find any instructions here so I'm uploading some.

*\*Please Ignore the goofy white borders, forgot to consider aspect ratio when taking the pictures\**

---

### TOOLS:

- [Phillips #0 Screwdriver](#) (1)
- [iFixit Opening Tools](#) (1)

### PARTS:

- [LG Volt Charging Port](#) (1)
-

## Step 1 — Power off and Unplug Phone



- Always power off and unplug your devices before servicing them.

## Step 2 — Remove Rear Cover



- There is a pry tab you can use your fingernail or a pry tool to remove the rear cover.

### Step 3 — Remove Battery & Sim Card



- Note the location of the screws to remove the inner rear panel.

## Step 4 — Remove Inner Rear Cover



- Remove the 11 screws on the inside rear cover using your Phillips screw driver.
- See photo from "Remove Battery" step for location of screws.
- Use your pry tool and carefully work your way around the inside rear cover to undo the snaps and remove it.

## Step 5 — Remove Charging Port / Daughter Board



- Disconnect the 3 cables and two screws before attempting to remove the charging port circuitry.
- **Beware the adhesive on the back!**

To reassemble your device, follow these instructions in reverse order.