



HP Pavilion 14-q020nr Wi-Fi Card Replacement

Replacement of the Wi-Fi card inside of the HP Pavilion 14-q020nr Chromebook.

Written By: Jenell Chase




INTRODUCTION

Wi-Fi cards are often replaced to gain faster internet connection. This guide where show you where the Wi-Fi card is located and how to replace it.

TOOLS:




- [Phillips #1 Screwdriver](#) (1)
 - [Tweezers](#) (1)
 - [iFixit Opening Tools](#) (1)
 - [Spudger](#) (1)
-

Step 1 — Keyboard & Touchpad Panel



- Turn the laptop over.
- Remove all nine 3mm screws on back panel with a Phillips Head 1 driver.

Step 2




- Pry off the four rubber bumpers, located at the top corners and center of the back panel, off with a pair of tweezers.
- ⚠ Bumpers are delicate and can be easily ripped.
- Unscrew the four 3mm screws under the bumpers using a Phillips Head 1 screwdriver.

Step 3






- Flip the laptop right side up and open the clamshell.
- Starting at the bottom right corner, slide the opening tool into the crevice between the blue and silver panels.
- Carefully pry the top casing up around the edges, moving counterclockwise.
- ⓘ Keep the tool steady throughout, as prying in a rough manner can break the casing.
- ⓘ You will hear audible clicking sounds as the clips connecting the two halves disconnect from each other.

Step 4



- Close the laptop and orient it on its side (clamshell hinge up), carefully holding it steady to ensure its safety.
- Insert the opening tool inside of the hinge and pry with an even amount of force to disconnect the keyboard panel from the fan grate.

Step 5




- Reorient the laptop in an upright fashion and open the clamshell.
- If needed, continue to pry the silver keyboard panel from the rest of the hardware with minimal force.
- Slowly slide the silver keyboard panel towards you while lifting gently to separate the halves.




The panel is still connected by a series of delicate connectors glued to the mainframe, so do not pull the panel right off.

Step 6




- While keeping silver keyboard panel hovering above the laptop, locate the touchpad connector ribbon attached to both the silver panel and motherboard.
- With your finger, flip up the white clasp that holds the connector, releasing the connector ribbon.
- Unpeel the connector ribbon from its position on the motherboard.

Step 7




- With your finger, flip up the white clasp that connects the larger keyboard connector to the motherboard, releasing the connector ribbon.
- Gently pull the connector ribbon from the clasp.

Step 8



- Lift the keyboard panel up and away from the CPU, completely revealing the mainframe.

Step 9 — Battery and Speakers





- With the internal hardware exposed, disconnect the battery cable from the motherboard.
- If tightly fastened, gently wiggle the plug out of the jack.

Step 10




- Remove the three 4mm screws around the perimeter of the battery pack with a Phillips Head 1 screwdriver.

Step 11




- Flip up the two white clasps that hold the connector ribbon to the battery to release the ribbon.
- Remove the 'motherboard to USB board' connector ribbon from its place.

Step 12



- Detach the speaker cable from its fastener on the motherboard by pulling it out with your fingers or using a spudger.

Step 13





- Using your fingers, gently pry out the two L-shaped speaker panels from between the external casing and battery pack.
- ⚠ Be sure to apply an evenly distributed upwards force on the speaker when lifting it out
- ⓘ Both speaker components (located adjacent to each other) will remain connected by a red cable after removal

Step 14




- Lift out battery pack.

Step 15 — Motherboard




- Remove the two Wi-Fi antenna cables that are attached to the Wi-Fi card by pulling them up.

Step 16




- Using your fingers, pull the cooling fan cable from its fastener on the motherboard

Step 17




- Remove the 3mm screw that holds down the Wifi mini-PCI card using a Phillips Head 1 driver.

Step 18




- Remove the three 3mm screws that hold the cooling fan in place using a Phillips Head 1 driver.

Step 19




- In the upper right hand corner of the device, remove the 6mm screw holding the PCB board in place by using a Phillips Head 1.

Step 20



- Remove the three 3mm screws from the surface of the motherboard using a Phillips Head 1.


Step 21



- Carefully lift the motherboard up towards the screen as if it was hinged on one side.

⚠ To prevent possible scratching, cover the screen with a cloth.

Step 22 — Wi-Fi Card



- Using your fingers, pull the Wi-Fi card located on the right side of the detached motherboard out of its place.

To reassemble your device, follow these instructions in reverse order.